

Scaffold board T&F228-1,5 03

Steel Z275

PcP steel scaffold boards for Tube and Fittings are lighter, at 14.5 kg than wood boards. This means safer handling with faster erection and dismantling times, meeting and exceeding all the requirements of Health and Safety regulations.



Specifications

PTV guidelines	36+ Low Slip Potential acc. to BS 7976
Dry PTV average	73 multi-directional acc. to BS 7976
Wet PTV average	51 multi-directional acc. to BS 7976
Slip resistance	R13 = slope >35° acc. to DIN 51130
Free area	28-32 %
Upward grip holes	dia. 14 mm
Downward drainage holes	dia. 8,5 mm
C-C grid	36 x 36 mm
Flange design	High Strength Rolled - HSR []
Load Class	6 at 1,2m transom centres acc. to EN 12811

Suitable application areas

Scaffolding

Scaffold Tube & Fitting

Accessories

Fixing Clip - Scaffold

Related products

Fixing Clip - Scaffold

Standard dimensions

Length (mm)	Width (mm)	Height (mm)	Weight (kg)	Load class	Item No.
1200	228	38	4.50	6	F404670400
1800	228	38	6.50	6	F404680400
2400	228	38	9.00	6	F404690400
3000	228	38	11.00	6	F404700400
3900	228	38	14.50	6	F404710400